



## Maryville, TN

### SCOPE

Model: AKC-350

Application: Activated Carbon Hydrocarbon Adsorber

### OPERATING CONDITIONS

Inlet Design Flow Rate:	<b>350</b>	scfm, (Std. 70°F/14.7 psia)
Inlet Design Pressure:	<b>100</b>	psig ( <b>125 psig maximum</b> )
Inlet Design Temperature:	<b>100</b>	° F ( <b>120° F maximum</b> )
Inlet Relative Humidity:	<b>&lt; 40</b>	% of saturation
System Design Pressure:	<b>200</b>	psig
Outlet Compressed Air Flow Rate:	<b>350</b>	scfm
Inlet Hydrocarbon Content at Design Conditions:	<b>0.03</b>	ppmw (mg/m <sup>3</sup> )
Outlet Hydrocarbon Content at Design Conditions:	<b>≤ 0.003</b>	ppmw (mg/m <sup>3</sup> )
Compressed Air Loss:	<b>0.11</b>	scfm
Decompression Air Losses:	<b>21.5</b>	scf
Service Life:	<b>9,270</b>	hours based on 3.0 ppmw inlet
Ambient Air Temperature:	<b>38</b>	°F (Min.); <b>120°F</b> (Max.)
System Pressure Loss with Clean, Dry Activated Carbon:	<b>2</b>	psid

### SYSTEM COMPONENTS

Prefilter (optional):	Coalescing filter with 0.01 µm element
Condensate Drain (optional):	Zero-loss Electronic Drain
After Filter (optional):	Particulate filter with 5 µm element
Final Filter:	Not applicable
Adsorbent Type:	Coal based activated carbon, 1,000 m <sup>2</sup> /gram BET surface area
Adsorbent Quantity:	146 lbs. dry
Desiccant Vessel:	ASME Section VIII Division 1, "U" stamped, 200 psig at 450°F
Controller Type:	Not applicable
Controller Model:	Not applicable
Energy Management System:	Not applicable
Residual Oil Indicator:	Johnson Controls A-4000-120 colorimetric indicator
Switching Valves:	Not applicable
Regeneration Blower:	Not applicable
Regeneration Heater:	Not applicable
Regeneration Cooler:	Not applicable
Piping:	2 In. NPS
Insulation:	Not insulated

### DRYER ASSEMBLY

Height:	84 inches
Width:	24 inches
Depth:	24 inches
Connection Size:	1½ In. NPT
Dryer Assembly Weight:	445 pounds (approximately)